

Procut S3 Front Mount Specifications

(A) Headstock
Linkage mounting has fixed or floating positions for perfect contour following.

(B) Gearbox
Three year warranty

(C) Belt adjustment
Simple positive adjustment for each drive belt.

(D) Cutting height
Infinitely variable, only one tool required.

(E) Blades
Trimax's exclusive LazerBladez™.
Exceptional blade and bolt life.
"Tilt-forward" design for exceptional performance in all conditions.

(F) Underbody design
Increased clearance copes with large volumes of cut material.
Individual baffles for even grass spread with minimal windrows.
Cutting chamber sweeps up over rear roller to minimise blockages.

(G) Large diameter roller
Mow across uneven ground with ease.
Inboard bearings with custom greasing system.

	P3 178	P3 210	P3 237
Cutting Width	1.74m (69")	2.06m (81")	2.32m (91")
Overall Width	1.88m (74")	2.2m (87")	2.46m (97")
Overall Length	1.62m (64")	1.62m (64")	1.62m (64")
Cut Height Range	10-110mm (3/8-4¼")	10-110mm (3/8-4¼")	10-110mm (3/8-4¼")
No. of Spindles	3	3	4
Approx. Weight	568kg (1252lbs)	623kg (1373lbs)	683kg (1505lbs)
Minimum Power	26kW (35hp)	30kW (40hp)	34kW (45hp)

(H) Body
Strong monocoque construction utilising 5mm steel.

(I) Spindles
Tapered roller bearings.
High tensile shafts.
Labyrinth seals.
Tapered housing.
Two year warranty on spindle assemblies.

(J) Remote spindle grease points
No need to lift covers.

(K) Transmission guards
Stainless steel for long life.

