

Jumbo Modular



Side flail mower for several for several appliances

The Votex Jumbo Modular is based on the Jumbo, but with a mowing head that can be extended with a straight outlet, a conveyor belt or an auger.

The Jumbo Modular is suitable for normal mowing, mowing of ditches with removing the clippings out of the ditch or mowing with aspirating the clippings into a trailer.

Like the standard Jumbo, the Jumbo Modular has several hydraulic adjustments, has several protections against peak load and has standard a safety break back system to the front and rear.

Specifications	120	150	190	230
Chassis				
Category	II/III			
Mounting	front or rear mounted			
Safety break back system	Mechanically to front and rear			
Side shift	Hydraulically by SWING-ON-LINE®			
Max. displacement (cm)	60			
Max. reach relative to axis tractor (cm)	274	310	346	382
Mowing angle (°)	-60 to +90			
Mowing head				
Model mowing head	Ecomow			
Flails				
Weight 40x12 flail (g)	325			
Amount 40x12 flails	36	48	60	72
Weight hammer flail (g)	1.300			
Amount hammer flails	12	16	20	24
Power train				
Min. PTO power (kW//HP)	35/48	40/55	50/68	60/82
PTO speed (RPM)	540/750/1000			
Gearbox	Silent box with spiral toothing			
Dimensions				
Cutting width (cm)	109	145	181	217
Overall width (cm)	186			
Weight (kg)	930	975	1.020	1.135

